

# TR 171

|                     |               |
|---------------------|---------------|
| <b>TIRE SIZE</b>    | <b>8 - 18</b> |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS        |
| <b>MACHINERY</b>    | TRACTOR       |
| <b>VERSION</b>      | STANDARD      |
| <b>TIRE TYPE</b>    | TT            |
| <b>LI/SS</b>        | 96 A8         |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94052660 | <b>RC (IN)</b> | 103.0           |
| <b>SW (IN)</b>  | 7.5      | <b>RIM REC</b> | W 6             |
| <b>OD (IN)</b>  | 33.3     | <b>RIM ALT</b> | W 7; 5.50 F     |
| <b>SLR (IN)</b> | 15.4     | <b>ECE</b>     | E11-106R-006170 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>38</b> |
| 25               | 1565      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.