


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>620/75 R 26</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / SPRIDARE / TRAKTOR / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94050444	<b>RC (IN)</b>	191.0
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	62.6	<b>ECE</b>	E11-106R-002993
<b>SLR (IN)</b>	28.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	5530	6370	7810	8530	9380	10220	11060	12010	-	-
25	5530	6370	7810	8530	9380	10220	11060	12010	-	-
20	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 LT	7420	8540	10470	11440	12570	13690	14830	16100	-	-
5 HT	5920	6820	8370	9140	10040	10930	11840	12860	-	-
5 CYC.	-	9090	11650	12780	14810	16250	17780	19310	19610	20420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.