

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>280/70 R 20</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVERIZADOR AGRÍCOLA / TRATOR /<br>VINDIMADORA / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS    |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 116 A8/B   |



## DIMENSÕES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94021970 | <b>RC (IN)</b> | 106.5          |
| <b>SW (IN)</b>    | 10.8     | <b>RIM REC</b> | W 9            |
| <b>OD (IN)</b>    | 35.4     | <b>RIM ALT</b> | W 8; W 10      |
| <b>SLR (IN)</b>   | 16.1     | <b>ECE</b>     | E4-106R-0064 1 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-----------|------|------|------|------|------|------|------|------|
| 30        | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| 25        | 1300 | 1490 | 1710 | 1930 | 2150 | 2370 | 2570 | 2760 |
| 20        | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |
| 5 LT      | 1740 | 2000 | 2290 | 2590 | 2890 | 3190 | 3440 | 3690 |
| 5 HT      | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.