


# RIDEMAX IT 697 (M+S)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/65 R 38 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRAKTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 166 D ; 170 A8   |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 590  | <b>RIM REC</b> | DW 18 L         |
| <b>OD (MM)</b>  | 1745 | <b>RIM ALT</b> | DW 20 B         |
| <b>SLR (MM)</b> | 795  | <b>ECE</b>     | E11-106R-005855 |
| <b>RC (MM)</b>  | 5315 | <b>SRI</b>     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 2490 | 3075 | 3605 | 4185 | 4715 | 5300 |
| 50         | 2690 | 3320 | 3895 | 4525 | 5095 | 5725 |
| 40         | 2820 | 3480 | 4080 | 4740 | 5340 | 6000 |
| 30         | 2990 | 3690 | 4325 | 5025 | 5660 | 6360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.