

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 6.00 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | HD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 83 A8 |
| LI/SS FREE ROLLING | 95 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 164 | RIM REC | 4.00 E |
| OD (MM) | 735 | RIM ALT | 4.50 E; 4½ K |
| SLR (MM) | 343 | ECE | E11-106R-005194 |
| RC (MM) | 2190 | PR | 6 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|------------|------|
| 10 FR | 965 |
| 25 FR | 820 |
| 30 FR | 775 |
| 40 FR | 690 |
| 10 DW | 680 |
| 25 DW | 575 |
| 30 DW | 545 |
| 40 DW | 485 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.