


AGRIMAX SPARGO

| | |
|--------------|--|
| TIRE SIZE | VF 380/90 R 50 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSIONS IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 390 | RIM REC | W13 B |
| OD (MM) | 1950 | RIM ALT | W12 B |
| SLR (MM) | 893 | ECE | E11-106R-006400 |
| RC (MM) | 5950 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 3010 | 3385 | 3700 | 3890 | 4075 | 4200 | 4325 | 4580 | 4765 | 4955 | 5145 | 5330 | 5455 | 5645 | 5770 | 6020 | 6275 |
| FROM 65 TO 40 | 3310 | 3725 | 4070 | 4275 | 4485 | 4620 | 4760 | 5035 | 5240 | 5450 | 5655 | 5865 | 6000 | 6210 | 6345 | 6620 | 6900 |
| 30 | 3375 | 3795 | 4150 | 4360 | 4570 | 4710 | 4850 | 5135 | 5345 | 5555 | 5765 | 5975 | 6120 | 6330 | 6470 | 6750 | 7035 |
| 20 | 3440 | 3870 | 4230 | 4445 | 4660 | 4805 | 4950 | 5235 | 5450 | 5665 | 5880 | 6095 | 6240 | 6455 | 6600 | 6885 | 7175 |
| 10 | 3640 | 4095 | 4475 | 4705 | 4930 | 5085 | 5235 | 5540 | 5765 | 5995 | 6220 | 6450 | 6600 | 6830 | 6980 | 7285 | 7590 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.