DATA SHEET

PRINTED ON
23-04-2026

AS 505

TIRE SIZE	**6.5/80 - 15**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ATTREZZI AGRICOLI / RIMORCHIO / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	92 A8
LI/SS FREE ROLLING	104 A8

DIMENSIONI IS STANDARD

SW (MM)	171	**RIM REC**	5.0
OD (MM)	695	**RIM ALT**	4½ K; 5 K; 5 J
SLR (MM)	325	**ECE**	E4-106R-002660
RC (MM)	2106	**PR**	8

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.80
10 FR	1260
25 FR	1070
30 FR	1010
40 FR	900
10 DW	880
25 DW	750
30 DW	705
40 DW	630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..