

# AGRIMAX FORTIS

**600/70 R 30****UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** TRAKTÖR**VERSION** SPECIAL**TIRE TYPE** TL

158 D ; 161 A8



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1602	<b>RIM ALT</b>	DW 18 L ; W 18 L
<b>SLR (MM)</b>	724	<b>ECE</b>	E4-106R-001400
<b>RC (MM)</b>	4810	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2040	2380	2680	2975	3275	3530	3910	4250
50	2145	2505	2815	3130	3440	3710	4110	4465
40	2220	2590	2915	3240	3565	3840	4255	4625
30	2350	2740	3085	3425	3770	4060	4500	4890
10 LT	2735	3190	3590	3990	4390	4730	5240	5695
10 HT	2350	2740	3085	3425	3770	4060	4500	4890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.