

# AW 708

|                           |                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>          | <b>400/60 - 15.5</b>                                                                                    |
| <b>UM</b>                 | IS STANDARD                                                                                             |
| <b>CONSTRUCTION</b>       | ⊠ BIAS                                                                                                  |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / REMORQUE |
| <b>VERSION</b>            | SPECIAL                                                                                                 |
| <b>TIRE TYPE</b>          | TT                                                                                                      |
| <b>LI/SS FREE ROLLING</b> | 149 A8                                                                                                  |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b> | AG 13.00        |
| <b>OD (MM)</b>  | 875  | <b>ECE</b>     | E11-106R-004255 |
| <b>SLR (MM)</b> | 380  | <b>PR</b>      | 18              |
| <b>RC (MM)</b>  | 2564 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>4.50</b> |
|-------------------|-------------|
| 10 FR             | 4550        |
| 25 FR             | 3870        |
| 30 FR             | 3640        |
| 40 FR             | 3250        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.