


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>340/80 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	144 A8/B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94052875	<b>RC (IN)</b>	126.5
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	11
<b>OD (IN)</b>	41.4	<b>RIM ALT</b>	W10; 11 SDC; W11; 12; 12 SDC
<b>SLR (IN)</b>	18.9	<b>ECE</b>	E11-106R-002969

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2970	3530	4010	4570	5130	5500	6170	-	-
25	2970	3530	4010	4570	5130	5500	6170	-	-
20	3170	3770	4300	4890	5490	5890	6610	-	-
15	3300	3910	4460	5080	5700	6110	6860	-	-
5 CYC.	3620	4450	5240	6020	6860	7460	8430	8900	9260
STATIC	5540	6820	8020	9240	10520	11430	12930	13630	14200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.