


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/85 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	183 D



DIMENSIONS IS STANDARD

SW (MM)	680	RIM REC	DW 23 B
OD (MM)	2160	RIM ALT	DW20B;DW21B
SLR (MM)	938	ECE	E11-106R-0011307
RC (MM)	6413	SRI	1025

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3980	4615	5250	5970	6605	7240	7960
FROM 65 TO 40	4375	5075	5775	6560	7260	7960	8750
30	4460	5175	5890	6690	7405	8120	8925
20	4550	5275	6005	6825	7550	8280	9100
10	4810	5580	6350	7215	7985	8755	9625
UPTO 30 CYC	4965	5755	6550	7445	8240	9035	9930
UPTO 15 CYC	5925	6875	7820	8890	9835	10785	11855
UPTO 10 CYC	6495	7530	8570	9740	10780	11820	12990
10HT	4460	5175	5890	6690	7405	8120	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.