


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>420/90 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	147 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94063857	<b>RC (IN)</b>	180.0
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	DW13
<b>OD (IN)</b>	59.8	<b>RIM ALT</b>	W 14 L
<b>SLR (IN)</b>	26.9	<b>ECE</b>	E11-106R-006021

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35
30	3670	4750	5830	6380	6780
25	3670	4750	5830	6380	6780
20	3920	5090	6250	6830	7260
5	5500	7130	8750	9570	10170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.