

AW 702

| | |
|---------------------------|--|
| TIRE SIZE | 6.00 - 16 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE |
| VERSÃO | STANDARD |
| TIRE TYPE | TT |
| LI/SS FREE ROLLING | 95 A8 |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94009862 | RC (IN) | 86.5 |
| SW (IN) | 6.7 | RIM REC | 4.00 E |
| OD (IN) | 28.4 | RIM ALT | 4.50 E; 4½ K |
| SLR (IN) | 13.1 | ECE | E4-106R-001958 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 40 |
|-----------|------|
| 5 FR | 2130 |
| 15 FR | 1810 |
| 20 FR | 1710 |
| 25 FR | 1520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.