

## SM 55 L5S

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>17.5 - 25</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | UNDERGROUND MINING VEHICLE /<br>LOW PROFILE DUMP TRUCK (LPDT)                          |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TL/TT</b>        | TL                                                                                     |



### DIMENSIONS US STANDARD

|                 |          |                 |                            |
|-----------------|----------|-----------------|----------------------------|
| <b>USA CODE</b> | 94025886 | <b>RIM REC</b>  | 14.00/1.5                  |
| <b>OD (IN)</b>  | 54.1     | <b>RIM ALT</b>  | 14.00/1.3 ; 14.00/1.4 (DC) |
| <b>SLR (IN)</b> | 24.8     | <b>PR</b>       | 20                         |
| <b>RC (IN)</b>  | 159.2    | <b>TRA CODE</b> | L5S                        |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 83    |
|-----------|-------|
| 5         | 18200 |
| 10        | 15800 |
| 15        | 14600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.