

AW 726

| | |
|---------------------------|----------------------------------|
| TIRE SIZE | 400/60 - 15.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | REMORCĂ / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 137 A8 |
| LI/SS FREE ROLLING | 149 A8 |



DIMENSIUNI IS STANDARD

| | | | |
|----------------|-----------------|-----------|----|
| SW (MM) | 400 | PR | 18 |
| OD (MM) | 875 | | |
| RIM REC | AG 13.00 | | |
| ECE | E11-106R-005341 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.50 |
|-------------------|-------------|
| 10 FR | 4550 |
| 25 FR | 3870 |
| 30 FR | 3640 |
| 40 FR | 3250 |
| 10 DW | 3220 |
| 25 DW | 2735 |
| 30 DW | 2575 |
| 40 DW | 2300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.