


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 900/65 R 46</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATTORE A ELEVATA POTENZA /<br>TRATTORE   |
| <b>VERSIONE</b>     | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 193 D  |



## DIMENSIONI US STANDARD

|                   |          |                |                  |
|-------------------|----------|----------------|------------------|
| <b>CODICE USA</b> | 94513734 | <b>RC (IN)</b> | 271.1            |
| <b>SW (IN)</b>    | 36.2     | <b>RIM REC</b> | DW 30B           |
| <b>OD (IN)</b>    | 91.1     | <b>ECE</b>     | E11-106R-0011166 |
| <b>SLR (IN)</b>   | 39.5     |                |                  |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                   | 11760 | 13600 | 15450 | 17530 | 19150 | 20760 | 23070 |
| <b>FROM 40 TO 25</b> | 12930 | 14960 | 16990 | 19270 | 21040 | 22820 | 25350 |
| 20                   | 13180 | 15260 | 17320 | 19640 | 21460 | 23270 | 25860 |
| 12                   | 13440 | 15550 | 17660 | 20030 | 21880 | 23720 | 26370 |
| 5                    | 14220 | 16450 | 18680 | 21190 | 23140 | 25100 | 27890 |
| <b>UPTO 20 CYC</b>   | 14670 | 16960 | 19270 | 21860 | 23870 | 25890 | 28770 |
| <b>UPTO 10 CYC</b>   | 17510 | 20260 | 23000 | 26100 | 28500 | 30910 | 34350 |
| <b>UPTO 5CYC</b>     | 19190 | 22200 | 25220 | 28600 | 31240 | 33870 | 37640 |
| 5 HT                 | 13180 | 15260 | 17320 | 19640 | 21460 | 23270 | 25860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.