


# AS 504

<b>TIRE SIZE</b>	<b>5.00 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	75 A8
<b>LI/SS FREE ROLLING</b>	88 A8



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94052011	<b>RC (IN)</b>	77.0
<b>SW (IN)</b>	5.5	<b>RIM REC</b>	3.50 D
<b>OD (IN)</b>	25.9	<b>RIM ALT</b>	3.00 D; 4.00 E; 4 J
<b>SLR (IN)</b>	12.1	<b>ECE</b>	E4-106R-001950

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	51
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.