

# AGRIMAX RT 855

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 520/85 R 38                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS                    |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 170 A8/B                                                                                 |



## DIMENSIONS IS STANDARD

|          |      |         |                   |
|----------|------|---------|-------------------|
| SW (MM)  | 516  | RIM REC | DW 16 L           |
| OD (MM)  | 1849 | RIM ALT | DW 18 L ; DD 16 L |
| SLR (MM) | 847  | ECE     | E4-106R-001411    |
| RC (MM)  | 5595 | SRI     | 875               |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 2170 | 2650 | 3255 | 3875 | 4440 | 4740 | 5220 | 5640 | 6000 |
| 40         | 2170 | 2650 | 3255 | 3875 | 4440 | 4740 | 5220 | 5640 | 6000 |
| 30         | 2325 | 2740 | 3490 | 4150 | 4755 | 5075 | 5590 | 6035 | 6420 |
| 10 LT      | 2910 | 3430 | 4365 | 5195 | 5950 | 6355 | 6995 | 7560 | 8040 |
| 10 HT      | 2325 | 2740 | 3490 | 4150 | 4755 | 5075 | 5590 | 6035 | 6420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.