

AW 708

| | |
|---------------------------|--|
| TIRE SIZE | 19.0/45 - 17 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 138 A8 |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94010233 | RC (IN) | 99.8 |
| SW (IN) | 18.5 | RIM REC | 16.00 |
| OD (IN) | 34.1 | ECE | E4-106R-002334 |
| SLR (IN) | 15.0 | PR | 10 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 33 |
|------------------|-----------|
| 5 FR | 7290 |
| 15 FR | 6190 |
| 20 FR | 5830 |
| 25 FR | 5200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.