

AS 504

TIRE SIZE	7.50 - 20
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	103 A8
LI/SS FREE ROLLING	116 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019373	RC (IN)	106.1
SW (IN)	8.2	RIM REC	5.50 F
OD (IN)	35.6	RIM ALT	4.50 E; 6.00 F; 5.00 F
SLR (IN)	16.6	ECE	E4-106R-002636

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	46
5 FR	3860
15 FR	3260
20 FR	3090
25 FR	2760
5 DW	2700
15 DW	2290
20 DW	2160
25 DW	1930

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.