

# XL GRIP (L3)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 16.0/70 - 20                                     |
| <b>UM</b>           | US STANDARD                                      |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | CARREGADORA / CARREGADORA /<br>TRATOR DE ESTEIRA |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSÕES US STANDARD

|                   |          |                 |        |
|-------------------|----------|-----------------|--------|
| <b>CÓDIGO USA</b> | 94030538 | <b>RIM REC</b>  | 13 SDC |
| <b>OD (IN)</b>    | 42.9     | <b>PR</b>       | 16     |
| <b>SLR (IN)</b>   | 18.9     | <b>TRA CODE</b> | L3     |
| <b>RC (IN)</b>    | 129.7    |                 |        |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58   | 75    |
|-----------|------|-------|
| 30        | 7750 | -     |
| 5         | -    | 12640 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.