


RIDEMAX FL 615

| | |
|---------------------|--|
| TIRE SIZE | VF 900/65 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SLÄPVAGN / TANKBIL / SPRIDARE / ARBETSFORDON |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 200 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 891 | RIM REC | DW 30 B |
| OD (MM) | 2115 | ECE | E11-106R-0011504 |
| SLR (MM) | 929 | SRI | 975 |
| RC (MM) | 6445 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------|-------|-------|-------|-------|-------|-------|
| 65 | 6860 | 7700 | 9380 | 10640 | 12320 | 14000 |
| 50 | 8030 | 9010 | 10975 | 12450 | 14415 | 16380 |
| 40 | 8850 | 9935 | 12105 | 13730 | 15895 | 18060 |
| 30 | 9675 | 10860 | 13230 | 15005 | 17375 | 19740 |
| 25 | 10020 | 11245 | 13695 | 15535 | 17990 | 20440 |
| 20 | 10430 | 11705 | 14260 | 16175 | 18730 | 21280 |
| 10 | 11255 | 12630 | 15385 | 17450 | 20205 | 22960 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.