

MP 567

| | |
|---------------------------|---|
| TIRE SIZE | 10.0/75 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO / ATTREZZI AGRICOLI / SOLLEVATORE TELESCOPICO / VEICOLO UNIVERSALE |
| VERSIONE | IMPLEMENT |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 123 A8 |
| LI/SS FREE ROLLING | 135 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 258 | RIM REC | 9.0 |
| OD (MM) | 774 | ECE | E11-106R-003607 |
| SLR (MM) | 365 | PR | 18 |
| RC (MM) | 2401 | | |

LOAD CAPACITY (KG/TIRE)

| | |
|-------------------|-------------|
| KM/H / BAR | 7.10 |
| 40 FR | 2180 |
| 40 DW | 1550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.