

AGRIMAX RT 657

TIRE SIZE	480/65 R 24
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	140 D ; 143 A8



DIMENSIONI IS STANDARD

SW (MM)	479	RIM REC	W 15 L
OD (MM)	1234	RIM ALT	W 14 L
SLR (MM)	562	ECE	E4-106R-000617
RC (MM)	3730	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1200	1400	1575	1750	1925	2075	2300	2500
50	1260	1470	1655	1840	2025	2180	2415	2625
40	1310	1530	1720	1910	2100	2265	2510	2725
30	1380	1610	1815	2015	2215	2390	2645	2875
10 LT	1610	1880	2115	2345	2580	2785	3085	3350
10 HT	1380	1610	1815	2015	2215	2390	2645	2875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.