


AGRIMAX RT 657

TIRE SIZE	440/65 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	138 D ; 141 A8



DIMENSIONS IS STANDARD

SW (MM)	441	RIM REC	W 14 L
OD (MM)	1283	RIM ALT	W 13; W 15 L
SLR (MM)	590	ECE	E4-106R-000767
RC (MM)	3927	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1135	1325	1490	1655	1820	1960	2175	2360
50	1195	1390	1565	1740	1910	2060	2285	2480
40	1240	1445	1625	1805	1985	2140	2370	2575
30	1305	1525	1715	1905	2095	2255	2500	2715
10 LT	1520	1775	1995	2220	2440	2630	2915	3165
10 HT	1305	1525	1715	1905	2095	2255	2500	2715

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.