

AGRIMAX RT 855

TIRE SIZE	320/85 R 34
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	141 A8/B



DIMENSIONS US STANDARD

CODE USA	94047239	RIM ALT	W 9 ; W 10
SW (IN)	13.0	ECE	E4-106R-000758
OD (IN)	55.4	TRA CODE	R1W
SLR (IN)	25.4	TREAD DEPTH (32nd)	52.29
RC (IN)	168.5	TMPH (TM/H)	0
RIM REC	W 11		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
30	2050	2390	3130	3810	4140	4430	4830	5220	5680
25	2050	2390	3130	3810	4140	4430	4830	5220	5680
20	2190	2560	3350	4080	4440	4750	5180	5600	6080
5 LT	2740	3210	4200	5100	5570	5940	6480	7010	7620
5 HT	2190	2560	3350	4080	4440	4750	5180	5600	6080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.