

# XL GRIP IND3 (RTG)

|                     |             |
|---------------------|-------------|
| <b>TIRE SIZE</b>    | 21.00 - 25  |
| <b>UM</b>           | US STANDARD |
| <b>CONSTRUCTION</b> | ⊠ BIAS      |
| <b>MACHINERY</b>    | RTG-KRAN    |
| <b>VERSION</b>      | INDUSTRIAL  |
| <b>TIRE TYPE</b>    | TL          |



## ABMESSUNGEN US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>USA-CODE</b> | 94063840 | <b>RIM REC</b>  | 15.00/3.0 |
| <b>OD (IN)</b>  | 68.9     | <b>RIM ALT</b>  | 17.00/3.0 |
| <b>SLR (IN)</b> | 31.1     | <b>PR</b>       | 44        |
| <b>RC (IN)</b>  | 204.1    | <b>TRA CODE</b> | IND3      |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>145</b> |
| 5                | 64300      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.