

FLOTATION 648

TIRE SIZE	600/55 - 26.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B



DIMENSIONS US STANDARD

CODE USA	94006434	RC (IN)	158.1
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	53.3	ECE	E4-106R-002277
SLR (IN)	22.9	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	26	29
5 FR	13430	14940	15890
10 FR	12080	13450	14310
20 FR	10740	11950	12720
25 FR	9590	10670	11350
30 FR	8630	9600	10200
5 DW	9520	10580	11260
10 DW	8560	9520	10140
20 DW	7620	8470	9020
25 DW	6800	7560	8050
30 DW	6120	6800	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.