


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>340/80 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	140 A8 ; 135 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	DW 11
<b>OD (MM)</b>	1154	<b>RIM ALT</b>	W 10 ; W 12 ; DW 10
<b>SLR (MM)</b>	521	<b>ECE</b>	E4-106R-002293
<b>RC (MM)</b>	3444	<b>SRI</b>	550

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	1025	1265	1480	1720	1940	2180
50	1105	1365	1600	1855	2090	2350
40	1175	1450	1700	1975	2225	2500
30	1220	1510	1770	2055	2315	2600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.