


# AS 504

<b>TIRE SIZE</b>	<b>7.50 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	94 A8
<b>LI/SS FREE ROLLING</b>	106 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	209	<b>RIM REC</b>	5.50 F
<b>OD (MM)</b>	854	<b>RIM ALT</b>	4.50 E; 6.00 F; 5.00 F
<b>SLR (MM)</b>	407	<b>PR</b>	6
<b>RC (MM)</b>	2649	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.30</b>
10 FR	1330
25 FR	1130
30 FR	1065
40 FR	950
10 DW	940
25 DW	795
30 DW	750
40 DW	670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.