

RIDEMAX FL 693 M



TIRE SIZE	500/45 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	146 D ; 143 E

РАЗМЕРЫ IS STANDARD

SW (MM)	503	RIM REC	AG 16.00
OD (MM)	1022	ECE	E4-106R-000786
SLR (MM)	455	SRI	500
RC (MM)	3114		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1000	1120	1390	1585	1830	2075	2265	2480	2725
65	1095	1230	1530	1740	2010	2280	2490	2730	3000
50	1330	1490	1855	2110	2435	2760	3015	3305	3630
40	1495	1675	2085	2370	2735	3105	3390	3715	4080
25	1735	1945	2420	2750	3180	3605	3935	4315	4740
10	1975	2215	2755	3135	3620	4105	4485	4915	5400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.