


# EARTHMAX SR 30

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 15.5 R 25  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DUMPER ARTICOLATO / DOZER / PALA CARICATRICE   |
| <b>VERSIONE</b>     | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 160 B ; 169 A2   |



## DIMENSIONI IS STANDARD

|                 |           |                    |       |
|-----------------|-----------|--------------------|-------|
| <b>OD (MM)</b>  | 1276      | <b>TRA CODE</b>    | E3/L3 |
| <b>SLR (MM)</b> | 574       | <b>STAR RATING</b> | ★★★   |
| <b>RC (MM)</b>  | 3809      |                    |       |
| <b>RIM REC</b>  | 12.00/1.3 |                    |       |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 | 5.25 |
|------------|------|------|------|------|------|------|
| 50         | 3650 | 3875 | 4000 | 4250 | 4375 | 4500 |
| 10         | 5000 | 5150 | 5450 | 5600 | 5800 | -    |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.