


# TRAC SUPER

<b>TIRE SIZE</b>	<b>440/50 R 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	МИНИ-ТРАКТОР / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	135 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94038534	<b>RC (IN)</b>	105.3
<b>SW (IN)</b>	17.4	<b>RIM REC</b>	14.00
<b>OD (IN)</b>	34.3	<b>RIM ALT</b>	13.00
<b>SLR (IN)</b>	15.6	<b>ECE</b>	E4-106R-000662

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52
40	2110	2120	2360	2790	3170	3600	4090	4380	4810
25	2870	2880	3210	3790	4320	4910	5570	5950	6540
20	3170	3200	3560	4220	4790	5460	6180	6610	7260
5	3790	3810	4240	5030	5720	6490	7360	7880	8650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.