



Latest update  
2-06-2026

## DATA SHEET

# EM 936

|                     |                         |
|---------------------|-------------------------|
| <b>TIRE SIZE</b>    | <b>16.0/70 -24</b>      |
| <b>UM</b>           | US STANDARD             |
| <b>CONSTRUCTION</b> |                         |
| <b>MACHINERY</b>    | TELEHANDLER / EXCAVATOR |
| <b>VERSION</b>      | STANDARD                |
| <b>TL/TT</b>        | TL                      |
| <b>LI/SS</b>        | 152 B ; 169 A2          |



### DIMENSIONS US STANDARD

|                 |          |                 |         |
|-----------------|----------|-----------------|---------|
| <b>USA CODE</b> | 94005369 | <b>RIM REC</b>  | 13 SDC  |
| <b>OD (IN)</b>  | 46.1     | <b>RIM ALT</b>  | 13 (DC) |
| <b>SLR (IN)</b> | 22.6     | <b>PR</b>       | 14      |
| <b>RC (IN)</b>  | 141.7    | <b>TRA CODE</b> | E2      |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 52   | 66    |
|-----------|------|-------|
| 30        | 7830 | -     |
| 5         | -    | 12790 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.