



IS standard



GROWING TOGETHER

COMMANDER TWIN RIB



PRODUCT DATA SHEET



Bias



Technologies



Deep Tread

Performance



Cut and Chip Resistance



Durability



High Load Capacity



COMMANDER TWIN RIB

COMMANDER TWIN RIB is a 4-rib pattern tire with shoulder notches providing excellent grip. Its wider tread profile ensures good weight distribution. The strong casing along with a superior tread compound provide a longer tire life. COMMANDER TWIN RIB is perfect for soil tillage and haulage applications.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	5.00 - 15	4.00 E	-	145	665	-	-	STD	6	TT	82 A6
Ø 16"	6.00 - 16	4.50 E	4.00 E; 5.00 F	170	750	-	-	STD	8	TT	94 A6
	6.50 - 16	4.50 E	4.00 E; 5.00 F; 5.50 F	180	761	-	-	STD	8	TT	98 A6
	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	210	810	-	-	STD	8	TT	103 A6
Ø 20"	6.50 - 20	5.00 F	4.00 E; 5.50 F	190	875	-	-	STD	8	TT	101 A6

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference