

FLOTATION 648

TIRE SIZE	600/55 - 26.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/157 B
LI/SS FREE ROLLING	172 A6/169 B



DIMENSIONS US STANDARD

CODE USA	94030972	RC (IN)	158.1
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	53.3	ECE	E11-106R-004556
SLR (IN)	22.9	PR	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	39	41	42
5 FR	18640	19050	19440
10 FR	16780	17140	17500
20 FR	14910	15230	15550
25 FR	13320	13600	13890
30 FR	11980	12250	12790
5 DW	13320	13610	13890
10 DW	11980	12250	12500
20 DW	10660	10890	11110
25 DW	9510	9720	9920
30 DW	8560	8750	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.