


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>IF 1250/50 R 32 CFO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE / STREUMASCHINE / ERNTEMASCHINE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	201 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	1247	<b>RIM REC</b>	VA44/1.7 (multipiece)
<b>OD (MM)</b>	2063	<b>ECE</b>	E11-106R-006958
<b>SLR (MM)</b>	897	<b>SRI</b>	975
<b>RC (MM)</b>	6136		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	6525	7395	9280	10295	11455	12325	13485	14500	---	---
40	7115	8065	10120	11225	12490	13435	14700	15805	---	---
30	7615	8630	10830	12010	13365	14380	15735	16915	---	---
10 LT	9535	10805	13560	15040	16735	18005	19700	21180	---	---
10 HT	7615	8630	10830	12010	13365	14380	15735	16915	---	---
UPTO 10 CYC WITH FRONT LOADER	---	11960	15320	16795	19485	21365	23380	25395	25800	26870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.