

# EM 937 E3 (L)

|                     |                   |
|---------------------|-------------------|
| <b>TYRE SIZE</b>    | <b>14.00 - 25</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | LOADER            |
| <b>VERSION</b>      | STEEL BELTED      |
| <b>TYRE TYPE</b>    | TT                |



## DIMENSIONS IS STANDARD

|                 |           |                 |       |
|-----------------|-----------|-----------------|-------|
| <b>OD (MM)</b>  | 1368      | <b>PR</b>       | 20    |
| <b>SLR (MM)</b> | 620       | <b>TRA CODE</b> | E3/L3 |
| <b>RC (MM)</b>  | 4105      |                 |       |
| <b>RIM REC</b>  | 10.00/1.5 |                 |       |

## LOAD CAPACITY (KG/TYRE)

| <b>KM/H / BAR</b> | <b>4.75</b> | <b>7.00</b> |
|-------------------|-------------|-------------|
| <b>40</b>         | 4765        | -           |
| <b>10</b>         | -           | 8500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.