


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>480/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	138 D ; 141 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94513819	<b>RC (IN)</b>	153.3
<b>SW (IN)</b>	19.1	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	51.6	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (IN)</b>	23.2	<b>ECE</b>	E11-106R-0011157

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2870	3340	3800	4280	4740	5200
30	3010	3510	4000	4490	4980	5470
25	3140	3650	4170	4670	5190	5700
15	3300	3840	4380	4920	5460	5990
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3300	3840	4380	4920	5460	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.