

AGRIMAX TURF RT 333

TIRE SIZE	480/70 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	140 A8 ; 140 B



РАЗМЕРЫ US STANDARD

USA CODE	94075393	RC (IN)	166.5
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	55.9	RIM ALT	W 14 L; W 16 L
SLR (IN)	24.8	ECE	E11-106R-009049

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	3040	3530	4030	4520	5020	5520
25	3040	3530	4030	4520	5020	5520
20	3260	3790	4310	4840	5370	5900
5 LT	4070	4730	5410	6070	6730	7390
5 HT	3260	3790	4310	4840	5370	5900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.