

# TR 117

**11.2 - 24**

|                     |  |
|---------------------|--|
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | ILAÇLAMA VE SULAMA MAKINESİ /<br>UYGULAMALI MAKİNE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 106 A8   |



## UNDEFINED US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94029082 | <b>RC (IN)</b> | 126.2          |
| <b>SW (IN)</b>  | 11.2     | <b>RIM REC</b> | W 10           |
| <b>OD (IN)</b>  | 42.9     | <b>RIM ALT</b> | W 9            |
| <b>SLR (IN)</b> | 20.0     | <b>ECE</b>     | E4-106R-001967 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 26   | 34   |
|-----------|------|------|
| 25        | 2090 | ---  |
| CREEP     | ---  | 4420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.