


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 710/60 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR DE ALTA POTENCIA / TRACTOR
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D

## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94053377	<b>RC (IN)</b>	227.8
<b>SW (IN)</b>	28.0	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	76.0	<b>RIM ALT</b>	DW 23 B; MW 25 B
<b>SLR (IN)</b>	33.9	<b>ECE</b>	E11-106R-002998

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7160	8340	9510	10690	11860	13040
<b>FROM 40 TO 25</b>	7880	9170	10460	11750	13040	14330
20	8040	9350	10660	11980	13290	14620
12	8190	9530	10870	12210	13560	14900
5	8660	10090	11500	12920	14340	15760
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	11030	12830	14640	16450	18250	20060
5 HT	8040	9350	10660	11980	13290	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.