

# AT 621

|                     |  |
|---------------------|--|
|                     | <b>33X12.5 - 15</b>                                    |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | KÜÇÜK YÜKLEYİCİ / BEKOLODER /<br>BEKOLODER / YÜKLEYİCİ |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## UNDEFINED IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 318  | <b>RIM REC</b>  | 10.00 F SDC     |
| <b>OD (MM)</b>  | 851  | <b>ECE</b>      | E11-106R-005230 |
| <b>SLR (MM)</b> | 394  | <b>PR</b>       | 8               |
| <b>RC (MM)</b>  | 2507 | <b>TRA CODE</b> | R4              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.25</b> |
| 10                | 2130        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.