

AGRIMAX RT 855

| | |
|---------------------|---|
| TIRE SIZE | 320/85 R 20 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 119 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 329 | RIM REC | W 11 |
| OD (MM) | 1052 | RIM ALT | W 9 ; W 10 |
| SLR (MM) | 467 | ECE | E4-106R-000645 |
| RC (MM) | 3100 | SRI | 500 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 750 | 875 | 995 | 1120 | 1240 | 1360 |
| 40 | 750 | 875 | 995 | 1120 | 1240 | 1360 |
| 30 | 805 | 935 | 1070 | 1200 | 1330 | 1460 |
| 10 LT | 1005 | 1170 | 1335 | 1500 | 1665 | 1825 |
| 10 HT | 805 | 935 | 1070 | 1200 | 1330 | 1460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.