

# AGRIMAX FORCE

|           |                                                   |
|-----------|---------------------------------------------------|
| TIRE SIZE | IF 710/70 R 42 CFO                                |
| UM        | US STANDARD                                       |
| MACHINERY | ERNTemaschine /<br>HOCHLEISTUNGSTRAKTOR / TRACTOR |
| VERSION   | STANDARD                                          |
| TIRE TYPE | TL                                                |
| LI/SS     | 179 D                                             |



## ABMESSUNGEN US STANDARD

|          |          |                                 |                |
|----------|----------|---------------------------------|----------------|
| USA-CODE | 94040926 | RIM REC                         | DW 25 B        |
| SW (IN)  | 28.2     | RIM ALT                         | DW 23 B        |
| OD (IN)  | 81.1     | ECE                             | E4-106R-001830 |
| SLR (IN) | 36.2     | TRA CODE                        | R1W            |
| RC (IN)  | 242.8    | TREAD DEPTH (32 <sup>nd</sup> ) | 77.49          |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 7300  | 8390  | 9630  | 10880 | 12120 | 13370 | 14600 | 15540 |
| FROM 40 TO 25 | 8020  | 9230  | 10590 | 11960 | 13330 | 14690 | 16060 | 17100 |
| 20            | 8340  | 9590  | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |
| 12            | 8660  | 9950  | 11430 | 12910 | 14380 | 15860 | 17340 | 18450 |
| 5             | 10180 | 11710 | 13450 | 15180 | 16920 | 18650 | 20390 | 21690 |
| UPTO 20 CYC   | 10430 | 11990 | 13770 | 15540 | 17320 | 19090 | 20880 | 22210 |
| UPTO 10 CYC   | 12430 | 14300 | 16410 | 18530 | 20650 | 22770 | 24890 | 26480 |
| UPTO 5 CYC    | 13630 | 15670 | 18000 | 20330 | 22650 | 24980 | 27290 | 29040 |
| 5 HT          | 8340  | 9590  | 11010 | 12430 | 13860 | 15280 | 16700 | 17770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.