


AGRIMAX TERIS

TIRE SIZE	520/85 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ХЛОПКОУБОРОЧНАЯ МАШИНА
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D



РАЗМЕРЫ IS STANDARD

SW (MM)	516	RIM REC	DW 16 L
OD (MM)	1951	RIM ALT	W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L
SLR (MM)	890	ECE	E4-106R-001829
RC (MM)	5851	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.8
65	1850	2185	2520	2800	3140	3420	3980	4540	5100	5600	-
50	1945	2295	2650	2940	3295	3590	4175	4765	5355	5880	-
40	2025	2395	2765	3070	3440	3745	4360	4970	5585	6135	-
30	2130	2515	2900	3220	3610	3930	4575	5250	5865	6440	-
25	2195	2590	2990	3320	3720	4055	4715	5380	6045	6640	-
10	2775	3280	3780	4200	4705	5125	5965	6805	7645	8400	-
10 CYC*	-	-	-	-	-	-	-	-	-	-	9520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.