


# AGRIMAX RT 955

<b>TYRE SIZE</b>	<b>210/95 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	120 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	214	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	1213	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	571	<b>ECE</b>	E4-106R-001391
<b>RC (MM)</b>	3703	<b>SRI</b>	575

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	645	830	1010	1095	1190	1305	1400	-
40	645	830	1010	1095	1190	1305	1400	-
30	690	885	1080	1170	1275	1395	1500	-
10	905	1180	1430	1555	1660	1830	1975	2100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.