

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8/ 148 B
<b>LI/SS FREE ROLLING</b>	164 A8/160 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	600	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1230	<b>ECE</b>	E11-106R-004553
<b>SLR (MM)</b>	540	<b>PR</b>	12
<b>RC (MM)</b>	3716		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500
10 DW	4080	4390	4830
20 DW	3675	3950	4345
30 DW	3265	3510	3865
40 DW	2915	3135	3450
50 DW	2625	2820	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.