


AGRIMAX V-FLECTO



| | |
|--------------|--|
| TIRE SIZE | VF 540/65 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR DE ALTA POTENCIA / TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 154 D |

DIMENSÕES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 549 | RIM REC | DW 20 B |
| OD (MM) | 1413 | RIM ALT | DW 18 L |
| SLR (MM) | 622 | ECE | E11-106R-005710 |
| RC (MM) | 4160 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------------------------|------|------|------|------|------|------|
| 70 | 1910 | 2250 | 2555 | 2865 | 3135 | 3410 |
| FROM 65 TO 40 | 2100 | 2475 | 2810 | 3150 | 3450 | 3750 |
| 30 | 2140 | 2520 | 2865 | 3210 | 3515 | 3825 |
| 20 | 2180 | 2570 | 2920 | 3275 | 3585 | 3900 |
| 10 | 2310 | 2720 | 3090 | 3465 | 3795 | 4125 |
| *UPTO 10 CYC WITH FRONT LOADER | 2940 | 3465 | 3930 | 4410 | 4830 | 5250 |
| 10 HT | 2140 | 2520 | 2865 | 3210 | 3515 | 3825 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.