

FLOTATION 648

TIRE SIZE	500/50 - 17
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	152 A8/148 B



DIMENSIONI US STANDARD

CODICE USA	94040353	RC (IN)	108.3
SW (IN)	20.1	RIM REC	16.00
OD (IN)	37.2	ECE	E4-106R-001886
SLR (IN)	16.4	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	45	46
5 FR	10560	10760	10960
10 FR	9500	9680	9870
20 FR	8440	8610	8760
25 FR	7540	7680	7830
30 FR	6790	6910	6940
5 DW	7220	7360	7500
10 DW	6500	6620	6750
20 DW	5780	5890	6000
25 DW	5160	5260	5360
30 DW	4640	4730	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.